

SEWAGE PUMPS



Sewage Pumps are rugged, non-clogging units designed to transport wastewater and solids-laden fluids without blockage. Featuring heavy-duty impellers, they are essential for municipal lift stations, basement drainage, and industrial effluent transfer where reliable handling of debris and slurry is critical.

Construction features

Pump body	Cast Iron (CI) / Stainless Steel
Impeller	CI
Motor Body	Cast Iron (CI) with cooling fins
Shaft	SS 316
Seals	Dual Mechanical Seals
Max. Solid Handling	Up to 25mm

Performance Chart

MODEL	HP	DEL. SIZE	PHASE	SOLID SIZE
XSWP-50	0.5	1"	SP	10
XSWP-100	1	2"	SP/TP	15
XSWP-150	1.5	2"	SP/TP	25
XSWP-200	2	2"	SP/TP	25
XSWP-300	3	2.5"	TP	25
XSWP-500	5	3"	TP	25
XSWP-750	7.5	4"	TP	25
XSWP-1000	10	4"	TP	25

MODEL	HP	3	5	7	8	10	12	14	16	18	20
XSWP-50	0.5	80	60	28	20						
XSWP-100	1	290	210	160	150	100					
XSWP-150	1.5	450	420	400	380	350	250	160	80		
XSWP-200	2			450	400	350	300	250	225	150	75
XSWP-300	3		650	580	500	350	200				
XSWP-500	5		1200	1150	1130	1000	925	750	500	300	
XSWP-750	7.5		1500	1450	1425	1250	1100	1000	800	400	
XSWP-1000	10			1800	1700	1600	1400	1200	900	600	350